

Product Details

Name: Male straight EPC-G/APC-G



产品特点/Characteristics

1. Quick installation, simple and flexible, space-saving.
2. The tube fitting comes in a wide variety of models to meet all your needs in pneumatic piping.
3. Even after installation, the direction of tubing can be changed freely.
4. The release ring adopts the ellipse design to make it more convenient and labor-saving for disconnection.
5. All taper pipe threads are pre-coated with Teflon with fine seal performance.
6. All fittings are equipped with the internal hexagonal holes. It is easy for them to be mounted in the narrow places.

技术参数/Specification

Fluid	Air, vacuum
Pressure Range	0~1.0MPa
Negative pressure	-100KPa(10Torr)
Max Pressure	1.5MPa
Temperature Rang	-15°C~80°C
Applicable Tube	Nylon(PA)Polyurethane(PU)

型号/MODEL	L	A	B	ΦD	G	H	内六角	X	Y	X1
EPC4-G01	19.3	14.9	5.5	4	G1/8	10	3.0	11.9	10.5	10
EPC4-G02	17.4	14.9	6.5	4	G1/4	10	3.0	11.9	10.5	10
EPC6-G01	20.2	16	5.5	6	G1/8	12	4.0	13.9	12.5	12
EPC6-G02	20.9	16	6.5	6	G1/4	12	4.0	13.9	12.5	12
EPC6-G03	19.5	16	7.5	6	G3/8	12	4.0	13.9	12.5	12
EPC6-G04	23	16	9.5	6	G1/2	14	4.0	13.9	12.5	12
EPC8-G01	27.1	18.2	5.5	8	G1/8	14	5.0	15.9	13.9	14
EPC8-G02	23	18.2	6.5	8	G1/4	14	6.0	15.9	13.9	14
EPC8-G03	22.1	18.2	7.5	8	G3/8	14	6.0	15.9	13.9	14
EPC8-G04	24.1	18.2	9.5	8	G1/2	14	6.0	15.9	13.9	14
EPC10-G01	28.9	20.3	5.5	10	G1/8	17	5.0	19.5	17	17
EPC10-G02	29.9	20.3	6.5	10	G1/4	17	6.0	19.5	17	17
EPC10-G03	25.9	20.3	7.5	10	G3/8	17	8.0	19.5	17	17
EPC10-G04	25.4	20.3	9.5	10	G1/2	17	8.0	19.5	17	17
EPC12-G01	31.6	22.7	5.5	12	G1/8	21	5.0	23	20.5	20
EPC12-G02	32.6	22.7	6.5	12	G1/4	21	6.0	23	20.5	20
EPC12-G03	34.6	22.7	7.5	12	G3/8	21	8.0	23	20.5	20
EPC12-G04	30.8	22.7	9.5	12	G1/2	21	8.0	23	20.5	20
EPC16-G03	36.1	25	7.5	16	G3/8	24	8.0	27	24	23.5
EPC16-G04	38.1	25	9.5	16	G1/2	24	10.0	27	24	23.5

