

Product Details



Name: EPV/APV

产品特点/Characteristics

- 1.Quick installation,simple and flexible,space-saving.
- 2.The tube fitting comes in a wide variety of models to meet all your needs in pneumatic piping.
- 3.Even after installatipn,the direction of tubing can be changed freely.
- 4.The release ring adopts the ellipse design to make it more convenient and labor-saving for disconnection.
- 5.All taper pipe threads are pre-coated with Teflon with fine seal performance.
- 6.All fittings are equipped with the internal hexagonal holes.It is easy for them to be mounted in the narrow places.

技术参数/Specification

Fluid	Air,vacuum
Pressure Range	0~1.0MPa
Negative pressure	-100KPa(10Torr)
Max Pressure	1.5MPa
Temerature Rang	-15°C~80°C
Applicable Tube	Nylon(PA)Polyurethane(PU)

型号/ MODEL	ΦD	Φd	E	X	Y	X1	C
EPV4	4	—	17.5	11.9	10.5	10	14.9
EPV6	6	3.3	18.8	13.9	12.5	12	15.5
EPV8	8	3.3	22.5	15.9	13.9	14	17.8
EPV10	10	4.3	27.2	19.5	17	17	20.5
EPV12	12	4.3	29.3	23	20.5	20	22.9
EPV16	16	4.3	32.5	27	24	23.5	24

