

26 Series LP

Type LP-019

Nom. Bore 19 mm

characteristic features:

- non squirt feature
- stainless steel version 1.4404/1.4571 or similar in smooth variant with gripping grooves instead of knurling (-GL/-GX)

optional features:

- GG = with ring grips (cast aluminium)
- OV = without valve
- SI = with additional axial safety lock (outer diameter 58 mm)
- VH= with locking aid

materials:

- standard:**
- 11 = steel, zinc plated
 - 21 = brass, passivated
 - 22 = brass, chrome plated
 - 01 = stainless steel 1.4404/1.4571 or similar

special materials:











- 13 = steel, chem. nickel plated
- 24 = brass, chem. nickel plated

seal qualities:









- 1 = NBR
- 2 = FKM
- 4 = EPDM

Please note the technical data on pages 2 - 7, 32 - 33 and the max. working pressures on page 9

Availability: ● Short ○ Medium ○ Long

	Part No.	Conne- tion A	steel zinc plated	brass passivated	brass chrome plated	AISI 316 ty/ 1.4571	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]	
Self sealing couplings	 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>	LP-019-O-WR026...-.	BSPP 3/4"	●	○	○				54	46	100	17		840	
		LP-019-O-WR033...-.	BSPP 1"	●	●	○				54	46	103	20		870	
	 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228, sealing profile "E" to DIN 3852-11 for o-ring or sealing ring.</p>	LP-019-O-WE026...-.	BSPP 3/4"	○						54	46	102	16		850	
		LP-019-O-VR026...-.	BSPP 3/4"	○						19	54	46	100	17		830
	 <p>BSPP male thread to DIN ISO 228/BS 5200 with 60° sealing cone</p>	LP-019-O-VR033...-.	BSPP 1"	○					19	54	46	103	20		870	
		LP-019-O-D1526...-.	M 26 x 1,5	○						15	54	46	95	12		830
	 <p>metric male thread with 60° sealing cone to DIN 7631</p>	LP-019-O-D1930...-.	M 30 x 1,5	○					19	54	46	97	14		830	
		LP-019-O-DV022...-.	M 30 x 1,5	○						19	54	46	128	45		920
	 <p>metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S)</p>	LP-019-O-L1826...-.	M 26 x 1,5	○				L	18	16	54	46	95	12		830
		LP-019-O-L2230...-.	M 30 x 2	○				L	22	20	54	46	97	14		830
LP-019-O-S2030...-.		M 30 x 2	○				S	20	16	54	46	99	16		850	
LP-019-O-S2536...-.		M 36 x 2	○				S	25	20	54	46	101	18		860	
 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228</p>	LP-019-O-WR526...-.	BSPP 3/4"	●	●	○				54	46	94	19		890		
	LP-019-O-WR533...-.	BSPP 1"	●	●	○				54	46	98	23		880		
 <p>hose connection</p>	LP-019-O-SL019...-.	19 mm	○	○	○				54	46	118	35		850		
	LP-019-O-SL025...-.	25 mm	○	○	○				54	46	123	40		870		
	LP-019-O-SL028...-.	28 mm	○	○	○				54	46	128	45		930		
Self sealing adaptors	 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>	LP-019-2-WR026...-.	BSPP 3/4"	●	○	○				54	46	96	17	32,5	690	
		LP-019-2-WR033...-.	BSPP 1"	●	●	○				54	46	99	20	32,5	720	
	 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228, sealing profile "E" to DIN 3852-11 for o-ring or sealing ring.</p>	LP-019-2-WE026...-.	BSPP 3/4"	○						54	46	98	16	32,5	700	
 <p>BSPP male thread to DIN ISO 228/BS 5200 with 60° sealing cone</p>	LP-019-2-VR026...-.	BSPP 3/4"	○					19	54	46	96	17	32,5	690		
	LP-019-2-VR033...-.	BSPP 1"	○					19	54	46	99	20	32,5	720		

Availability: ● Short ○ Medium ○ Long

	Part No.	Connection A	steel zinc plated	brass	passivated brass chrome plated	AISI 316 Ti/1.4571	series	pipe OD	n. b.	d	SW	l	t	n	weight [g]
			●	○	○	○									
Self sealing adaptors	 <p>metric male thread with 60° sealing cone to DIN 7631</p>	LP-019-2-D1526...-.	M 26 x 1,5	●	○	○			15	54	46	91	12	32,5	680
		LP-019-2-D1930...-.	M 30 x 1,5	●	○	○			19	54	46	93	14	32,5	680
	 <p>metric male thread with 60° sealing cone to DIN 7631, extended thread for bulkhead mounting, max. thickness 10mm</p>	LP-019-2-DV022...-.	M 30 x 1,5	○	○	○			19	54	46	124	45	32,5	770
		 <p>metric male thread with 24° sealing cone to DIN 2353 (light duty series L, heavy duty series S)</p>	LP-019-2-L1826...-.	M 26 x 1,5	●	○	○	L	18	16	54	46	91	12	32,5
	LP-019-2-L2230...-.		M 30 x 2	●	○	○	L	22	20	54	46	93	14	32,5	670
	LP-019-2-S2030...-.		M 30 x 2	●	○	○	S	20	16	54	46	95	16	32,5	690
LP-019-2-S2536...-.	M 36 x 2		●	○	○	S	25	20	54	46	97	18	32,5	710	
 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228</p>	LP-019-2-WR526...-.	BSPP 3/4"	●	●	○				54	46	90	19	32,5	740	
	LP-019-2-WR533...-.	BSPP 1"	●	●	○				54	46	94	23	32,5	730	
	 <p>hose connection</p>	LP-019-2-SL019...-.	19 mm	●	●	○				54	46	114	35	32,5	700
LP-019-2-SL025...-.		25 mm	●	●	○				54	46	119	40	32,5	710	
LP-019-2-SL028...-.		28 mm	●	●	○				54	46	124	45	32,5	780	
Thru type adaptors	 <p>British standard pipe parallel (BSPP) male thread to DIN ISO 228</p>	LP-019-1-WR021...-.	BSPP 1/2"	●	●	○			40	36	57,5	15	32,5	210	
		LP-019-1-WR026...-.	BSPP 3/4"	●	●	○			40	36	59,5	17	32,5	220	
		LP-019-1-WR033...-.	BSPP 1"	●	●	○			40	36	62,5	20	32,5	260	
	 <p>British standard pipe parallel (BSPP) female thread to DIN ISO 228</p>	LP-019-1-WR526...-.	BSPP 3/4"	●	●	○			40	36	57,5	19	32,5	240	
		LP-019-1-WR533...-.	BSPP 1"	●	●	○			45	41	61,5	23	32,5	250	
	 <p>hose connection</p>	LP-019-1-SL019...-.	19 mm	●	○	○			32			68,5	35	32,5	180
LP-019-1-SL025...-.		25 mm	●	○	○			32			73,5	40	32,5	190	

Series LP