

characteristic features:

- stainless steel version 1.4404/1.4571 or similar
 in smooth variant with gripping grooves instead
 knurling (-GL/-GX)

optional features:

OV = without valve

materials:
standard:

11 = steel, zinc plated
 21 = brass, passivated
 22 = brass, chrome plated
 01 = stainless steel 1.4404/1.4571 or similar

special materials:







13 = steel, chem. nickel plated
 24 = brass, chem. nickel plated

seal qualities:

1 = NBR
 2 = FKM
 4 = EPDM

Please note the
 technical data on
 pages 2 - 7, 32 - 33 and the
 max. working pressures
 on page 9

Availability: ● Short ● Medium ○ Long

| | Part No. | Conne- tion A | steel zinc | brass | brass chrome | ANSI 316 | series | pipe OD | n. b. | d | SW | l | t | n | weight [g] |
|------------------------|---|---|------------------------|------------|--------------|----------|--------|---------|-------|----------|----------|--------------|----------|--------------|------------|
| | | | plated | passivated | plated | 1.4571 | | | | | | | | | |
| Self sealing couplings |  <p>British stan- dard pipe parallel (BSPP) male thread to DIN ISO 228</p> | SP-009-0-WR017-... SP-009-0-WR021-... | BSPP 3/8" BSPP 1/2" | ● ● | ● ● | ○ ○ | ○ ○ | | | 28 28 | 25 25 | 71 71 | 12 15 | | 180 190 |
| | |  <p>British stan- dard pipe parallel (BSPP) fe- male thread to DIN ISO 228</p> | SP-009-0-WR521-... | BSPP 1/2" | ● | ● | ○ | ○ | | | 28 | 27 | 71 | 17 | |
| |  <p>hose connection</p> | SP-009-0-SL013-... | 13 mm | ● | ● | ○ | ○ | | | 28 | 25 | 86 | 30 | | 180 |
| Self sealing adaptors |  <p>British stan- dard pipe parallel (BSPP) male thread to DIN ISO 228</p> | SP-009-2-WR017-...-Z02 SP-009-2-WR021-...-Z02 | BSPP 3/8" BSPP 1/2" | ● ● | ● ● | ○ ○ | ○ ○ | | | 28 28 | 25 25 | 69,5 69,5 | 12 15 | 23,5 23,5 | 120 130 |
| | |  <p>British stan- dard pipe parallel (BSPP) fe- male thread to DIN ISO 228</p> | SP-009-2-WR521-...-Z02 | BSPP 1/2" | ● | ● | ○ | ○ | | | 28 | 27 | 69,5 | 17 | 23,5 |
| |  <p>hose connection</p> | SP-009-2-SL013-...-Z02 | 13 mm | ● | ● | ○ | ○ | | | 28 | 25 | 84,5 | 30 | 23,5 | 130 |